

AC控制迴路熔絲

額定電壓: AC500V, 額定遮斷容量: 100KA

標準規格: VDE 0636, IEC 269, 標記: gL, gG, aM



尺寸	適用之 熔絲底座	額定電流	訂購編號	包裝單位數量	大約重量/ 100個(KG)
10×38	RT18-32	2	1038002	10	0.9
		4	1038004		
		6	1038006		
		10	1038010		
		16	1038016		
		20	1038020		
		25	1038025		
		32	1038032		
14×51	RT18-63	2	1451002	10	2.2
		4	1451004		
		6	1451006		
		10	1451010		
		16	1451016		
		20	1451020		
		25	1451025		
		32	1451032		
		40	1451040		
		50	1451050		
22×58	RT18-125	10	2258010	10	6.0
		16	2258016		
		20	2258020		
		25	2258025		
		32	2258032		
		40	2258040		
		50	2258050		
		63	2258063		
		80	2258080		
		100	2258100		

RT18N fuse holder with neutral line connection

- Designed with two pairs of connecting terminal, one for live and the other for neutral.
- Rated insulating voltage: 660V AC, 50Hz
Rated working voltage: 250V and 415V AC, 50Hz
Rated current: 10, 16, 20, 25, 32A
- Equipped with static contacts and holding heads of different sizes, the product is able to hold five different sizes of cylindrical fuse links: 8.5 × 23, 8.5 × 32.5, 10.3 × 25.5, 10.3 × 31.5, 10.3 × 38
- Applicable for protection against overload or short-circuit of single phase equipment or for electrical isolation.
- Conforming to IEC269, IEC947-3, GB13539 and GB14048.3.
- Standard rail installation.
- High reliability, compact in size, excellent appearance, convenient while using result in wide application in industry, agriculture, electrics, telecommunication, transportation and construction, etc.